

Pro Bundle 1

HF6060

10 MHz – 6 GHz
Peak Power Detector – 6GHz (Opt)
Level Min -100dbm (Typical -110dbm)
Level Max 0dbm
Attenuation “Auto”, 0, 10, 20, 30dB
Filter Bandwidth Min 3KHz
Filter Bandwidth Max 50MHz
0.5PPM Stability
Accuracy +/- 2dB (typical)
Real-time PC Analysis
Unlimited Marker Points
Peak, RMS and Hold Functions
Internal & PC Logging



NF5030

1Hz – 1MHz
Typical Noise Level Min
0.1 V/m, 1 pT
Typical range Max 20k V/m,
100 μ T
Filter Bandwidth Min 1Hz
Filter Bandwidth Max 1MHz
Typical Accuracy
(base unit) 3%
Real-time PC Analysis
Unlimited Marker Points
Internal & PC Logging



The HyperLOG 7060

The included HyperLOG 7060 is a LOG Periodic directional antenna covering 700MHz to 6GHz. The antenna can mount directly to the HF6060 analyzer for “one-hand use,” or it can be connected via the included SMA cable.

The HyperLOG antennas are made to fit your demanding broadband applications. Each antenna is equipped with top quality gold-coated elements providing excellent linearity over the entire frequency range. They are sealed within an advanced technology radome housing offering protection against mechanical damage, oxidation and corrosion and against environmental influences that could affect consistent measurement readings.



Included Accessories for All HF Systems:

Rubber Rod, Omni Antenna
MiniTripod Stand/Pistol Grip
1 Meter SMA Cable
SMA to SMA Coupler

Plastic SMA Wrench
6-foot USB Cable
Installed Rechargeable Battery
Universal AC Adapter/Charger
Aluminum Carrying Case